



309.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Celeron Processor BayTrail-M N2910/N2920
- 2 *DDR3L 1066MHz Single CH SO-DIMM up to 8GB
- Support 2 * Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- Integrated 1 * 24-bits Dual CH LVDS
- Supports 1 * Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- Support Watch dog Technology
- Thin Mini-ITX Form Factor(17cm x 17cm)
- Slim & Fanless design, within 2cm height

CPU	Intel Celeron Processor BayTrail-M N2910/N2920
Chipset	INTEL® Bay Trail-M SoC Processor
Memory	2 *DDR3L 1333/1066MHz Single CH SO-DIMM up to 8GB
Expansion Slots	1 * PCI-E x 1 slot 1 * MINI PCI-E
Storage	2 * Serial ATAll (3Gb/s) connectors (One share with mSATA) 1 * mSATA socket (Share with one SATA port)
Audio	Realtek ALC662 2-Channel HD Audio
Ethernet LAN	1 * RTL8111G PCI-E Gigabit LAN
LVDS	1 * 24-bits Dual CH LVDS connector
USB	Embedded 3 * USB 3.0 + 5 * USB 2.0/1.1
Special Features	Support ACPI S3 Support CPU Smart FAN Support Watch Dog
Rear Panel I/O	1 * USB 3.0 port 3 * USB 2.0/1.1 ports 1 * RJ-45 port 1 * DVI-I port 1 * COM port (Support RS232/422/485) 1 * Line-out connector 1 * 4-pin 9V~36V DC in jack

• Internal I/O	• 1 * USB 3.0 header for 2 USB 3.0 ports • 1 * USB 2.0/1.1 header for 2 USB 2.0 ports • 1 * KB/MS header • CPU smart Fan / System Fan headers • 1 * LVDS header & 1 * GPIO header & 1 Parallel header • 3 * COM headers & 4 * COM ports 5V/12V Selectable headers • 1 * AUDIO AMP & 1 * AUDIO header & 1 * SPDIF header • 1 * chassis intrusion header & 1 * AT mode selectable header
• BIOS	• AMI 64MB SMT Flash ROM
• Form Factor	• Thin Mini ITX Form Factor (170mm x 170mm)
• Functional	• Panel PC, ATM, Security, KIOSK, POS, General Application, Transportation
• Certificate	• CE, FCC, RoHS
• Temperature	• Operating within 0~60 centigrade • Storage within -20-85 centigrade